

PRODUCT FACT SHEET

SYCLONE® JR. RECHARGEABLE AREA LIGHT

MARKET

APPLICATIONS: Law Enforcement, Sporting Goods, Security, Fire & Rescue, Hardware/Tool, Automotive, Industrial, Consumer

DESCRIPTION: The Syclone® Jr. has high and low outputs and uses a cool white LED for max illumination. The body can rotate

360° in its frame and is adjustable using one hand. The light will stand on its base and includes magnets that will hold it on any ferrous metal surface (in any orientation) to provide task-specific illumination. There is also a folding hook to hang the light with for added versatility. The rechargeable battery results in one of the lowest operating costs of any area light of this type and size. Battery charging is effortless — just pull open

the rubber USB cover and plug in the charge cord.

CASE MATERIAL: Tough thermoplastic construction with an elastomer button

DIMENSIONS: Length: 2.04 in. (5.18 cm) Width: 2.25 in. (5.71 cm) Thickness: 1.14 in. (2.89 cm)

WEIGHT: 2.0 oz (57 g)

LENS: Acrylic, gasket sealed

LIGHT SOURCE: LED technology, impervious to shock with a 50,000-hour lifetime

LIGHT OUTPUT: See chart. Optimized electronics provides regulated intensity.

210 1550 cd 79m

ON/OFF: Depress the button momentarily to turn the light on. The light will come on in high mode. Press the button

again and switch to low mode. The third press of the button will turn the light off. **NOTE:** If you wait more than two (2) seconds after the last button press, the next press of the button will turn the light off.

RUN TIME: See chart.

BATTERY: 1000 mAh Li-Polymer cell

CHARGING: Charge time is 4.5 hours with an AC wall charger (5V/1A USB input). Charge times will vary when using just

the USB/micro-USB cord, depending on the voltage the USB source provides. Charge indication is provided in

the on/off button. Red is charging, green is charged.

FEATURES: LED technology for extreme brightness IPX4-rated for water resistant operation 2-meter impact resistance tested

2-meter impact resistance tested

Micro-USB rechargeable

WARRANTY: Streamlight warrants its Syclone® Jr. "non-replaceable 1000mAh lithium polymer battery rated at 300-400

discharges" will be free from manufacturing defects under normal use for 24 months after purchase. During the warranty period, at its sole discretion, Streamlight will repair or replace any defective part or product.

BC CEC Compliant

OPTIONAL ACCESSORIE

ACCESSORIES: N/A

	FL1 STANDARD	HIGH	LOW
OUTPUT	31/5	210 LUMENS	85 LUMENS
RUN TIME	0	3h 45m	8h 30m
DISTANCE		79m	49m
INTENSITY		1550cd	600cd

PERFORMANCE CURVE

210 HIGH RUNTIME

85 LOW RUNTIME

21

8.5

4 HOURS

6 7 8

All performance claims to ANSI/PLATO FL1-2019 Standard

Issued: 08/13/2020