




**TLR® RM 1 HL-X****COMPACT, HIGH-LUMEN, RAIL-MOUNTED TACTICAL LIGHT**

- DESCRIPTION:** Lightweight & compact, the TLR® RM 1 HL-X features 1,000 lumens and 22,000 candela when powered by (1) Streamlight SL-B9® proprietary lithium-ion rechargeable battery pack. The ergonomic, multi-function tail switch provides momentary and constant on modes, in addition to push-button and remote pressure switch operation. The light attaches securely to any long gun with MIL-STD-1913 (Picatinny) rails.
- CASE MATERIAL:** Body and face cap: 6000 Series machined aircraft aluminum with Type II Mil-Spec anodized finish. Available in Black.  
Switch housing: Impact- and chemical-resistant high-impact engineered polymer
- DIMENSIONS:** Length: 3.64 in (9.25 cm)      Width: 1.18 in (3.0 cm)      Height: 1.50 in (3.81 cm)
- WEIGHT:** SL-B9®: 3.12 oz (88.5 g) with battery (included in purchase)  
CR123A: 3.02 oz (85.6 g) with battery
- LENS:** High temperature, shock-mounted, AR-coated, impact-resistant BOROFLOAT® glass
- LIGHT SOURCE:** White LED, impervious to shock with a 50,000-hour lifetime.
- LIGHT OUTPUT:** SL-B9®: 1,000 lumens, 22,000 candela peak beam intensity, and 297m beam distance.  
CR123A: 500 lumens, 11,000 candela peak beam intensity, and 210m beam distance.
- ON/OFF:** Multi-function, push-button tactical tail switch or remote pressure switch.  
Quick press for constant on operation and press and hold for momentary operation.  
Double tap switch within ¼ second to activate strobe (if enabled).  
Face cap offers “safe off” mode to prevent unintentional activation.
- RUN TIME:** SL-B9®: 30 minutes continuous operation to 10% output level.  
CR123A: 1.5 hours continuous operation to 10% output level.
- BATTERY:** SL-B9®: (1) Streamlight Li-Ion 850mAh USB-C rechargeable battery pack with integrated safety circuit, rechargeable up to 500 cycles. Charges within 2.5 hours via USB-C cord or optional bank charger.  
CR123A: (1) 3-volt CR123A lithium battery with a storage life of 10 years.
- FEATURES:** High-lumen operation with SL-B9® Li-Ion rechargeable battery pack.  
Multi-fuel operation; SL-B9® Li-Ion rechargeable battery pack or CR123A.  
Ambidextrous operation.  
Securely fits a broad range of weapons using key kit provided.  
Extensively live fire tested.  
Operating temperature: -4° F to +120° F (SL-B9®) or -40° F to +120° F (CR123A).  
IPX7-rated design; waterproof to 1 meter for 30 minutes.  
Serialized for positive identification.
- APPROVALS:**   Meets applicable United Kingdom and European Community Directives  
 CEC Compliant (with SL-B9® only)
- WARRANTY:** Streamlight's Limited Lifetime Warranty
- OPTIONAL ACCESSORIES:** Mounting adapters, remote switches, SL-B9® Li-Ion Battery Bank Charger